



# CCP ENTERPRISES

## FINE SCREW SCREEN

The fine screw screen will be manufactured in SS304 or SS316 with an hole opening of 2 mm to 5 mm punched hole. The Rotating screw will have a spiral welded to it with brush on lower end to clean the filtration media and suitably so as to convey the suspended solids in the forward direction. Moc of screw is carbon steel hot deep galvanized or Epoxy painted. as shaft rotates brushes wipe the solids from perforated area and travel to the outlet of the screens Simultaneously clean the perforated filter media.

### Feature :

- Continues Operation
- Capacity up to 100 m3/hr.
- Bar Spacing/ Hole opening from 2 mm to 6 mm
- Available in SS304 & SS316
- Easy / Channel installation
- Less space required
- Low power required
- Very less maintenance

| Model | Opening<br>2 mm | Opening<br>6 mm |
|-------|-----------------|-----------------|
| FS1   | 8 m3/h          | 20 m3/h         |
| FS2   | 20 m3/h         | 45m3/h          |
| FS3   | 32 m3/h         | 70 m3/h         |
| FS4   | 40 m3/h         | 80 m3/h         |



### CCP ENTERPRISES

Block No.404-Sentosa Pearl Waked Pune 411057

Email: [ccp.enterprises1@gmail.com](mailto:ccp.enterprises1@gmail.com)

[pravin1747@gmail.com](mailto:pravin1747@gmail.com)

<http://www.ccp-india.com>

Mob: +91 8087317595

+91 9373126260